

GR 98 P 8173

- 17 -

## Patent Claims

1. A vehicle communication system which has:  
at least one processor unit (1), arranged in the  
vehicle, for controlling applications (15),  
a plurality of different data sources (2, 4, 5, 6,  
8) which are connected to the processor unit (1),  
a plurality of operator consoles (9) which are  
connected to the processor unit (1) and have user  
interfaces for accessing the applications (9) and  
for data playback, and  
a central system controller (17) having a priority  
management system (19) which allocates, to the  
individual operator consoles (9), access rights  
with different degrees of priority to the  
applications (15).
2. The vehicle communication system as claimed in  
claim 1, characterized in that functions (16) which are  
implemented on the processor unit (1) or on a data  
source (2, 4, 5, 6, 8) are assigned to the applications  
(15).
3. The vehicle communication system as claimed in one  
of the preceding claims, characterized by an operator  
console controller (20.1, 20.2) with which the  
individual operator consoles (9) can be individually  
configured.
4. The vehicle communication system as claimed in the  
preceding claim, characterized in that the priority  
management system (19) allocates to the applications  
(15) individual access rights to a data bus (12) and/or  
to the processor unit (1).
5. The vehicle communication system as claimed in the  
preceding claim, characterized in that the priority  
management system (19) allocates to the applications  
(15) access to the data bus (12) as a function of the  
loading of the data bus (12) at that time.

GR 98 P 8173

- 18 -

Sub-A2

6. The vehicle communication system as claimed in one of claims 4 or 5, characterized in that when a defined load of the data bus (12) is reached or exceeded, at least one low-level application can be aborted or its data transmission rate can be reduced.
7. The vehicle communication system as claimed in one of claims 4 to 6, characterized in that the access of an application (15) to the data bus (12) can be controlled as a function of the priority of the requesting operator console (9).
8. The vehicle communication system as claimed in one of the preceding claims, characterized in that the operator console controller (20.1, 20.2) allocates individual access rights to the applications (15) for the access to an operator console (9).
9. The vehicle communication system as claimed in one of the preceding claims, characterized in that a user interface (22) of an operator console (9) can be configured individually by the operator console controller (20.1, 20.2).
10. A method for exchanging data in a vehicle, in which at least one processor unit (1) and a plurality of data sources (2, 4, 5, 6, 8) communicate with operator consoles (9) via a data bus (12),
- 25 - different applications (15) being controlled by the processor unit (1) so that they output onto different output devices (21)
  - access rights to the applications (15) being allocated to the operator consoles (9),
  - 30 - access rights with different degrees of priority to the applications (15) being allocated to the individual operator consoles (9).

005534 1100

GR 98 P 8173

- 19 -

11. The method as claimed in the preceding claim, characterized in that an operator console controller (20.1, 20.2) controls one or more of the following functions individually for an operator console (9):

- 5 - user prompting at the man/machine interface,  
assignment of running applications or their menus  
to defined positions of a display device,  
assignment of the access right of applications to  
an output device of the operator console.